

PERFORMANCE CURVE

Models:
HE3P6
PE3P6
SE3P / S3P

Back-Pull-Out Casing
3-Blade Impeller
3" Discharge
6" Suction
Variable Speed Curve

CURVE	POWER (HP/KW)	SPEED (RPM)	IMPELLER DIAMETER
A	60 / 45	2900	10.30" (262mm)
B	50 / 37	2720	10.30" (262mm)
C	40 / 30	2500	10.30" (262mm)
D	30 / 22	2200	10.30" (262mm)
E	25 / 18.5	2050	10.30" (262mm)
F	20 / 15	1900	10.30" (262mm)
G	20 / 15	1750	10.30" (262mm)
H	10 / 7.5	1460	10.30" (262mm)
I	7.5 / 5.5	1325	10.30" (262mm)
J	7.5 / 5.5	1170	10.30" (262mm)
K	5 / 4	970	10.30" (262mm)

DO NOT OPERATE PUMP IN DOTTED PORTION OF CURVES. PUMPS MAY EXCEED HP SHOWN IF OPERATED IN DOTTED PORTION OF CURVE. CURVES ARE SUBJECT TO CHANGE WITHOUT NOTICE. EFFICIENCIES SHOWN ARE NOMINAL BOWL. GUARANTEED MINIMUM EFFICIENCIES PER H.I. LEVEL A.

CAPACITY (CUBIC METERS PER HOUR)

