

PERFORMANCE CURVE

Models:
HE4S6
PE4S6
SE4S

Back-Pull-Out Casing
3-Blade Impeller
4" Discharge
6" Suction

CURVE	POWER (HP/KW)	SPEED (RPM)	IMPELLER DIAMETER
A	60 / 45	1900	11.80" (300 mm)
B	50 / 37	1825	11.80" (300 mm)
C	50 / 37	1770	11.80" (300 mm)
D	40 / 30	1675	11.80" (300 mm)
E	30 / 22	1525	11.80" (300 mm)
F	30 / 22	1460	11.80" (300 mm)
G	25 / 18.5	1400	11.80" (300 mm)
H	20 / 15	1325	11.80" (300 mm)
I	15 / 11	1180	11.80" (300 mm)
J	10 / 7.5	970	11.80" (300 mm)
K	7.5 / 5.5	870	11.80" (300 mm)
L	5 / 4	700	11.80" (300 mm)
M	5 / 4	500	11.80" (300 mm)

DO NOT OPERATE PUMP IN DOTTED PORTION OF CURVES. PUMPS MAY EXCEED HP SHOWN IF OPERATED IN DOTTED PORTION OF CURVE. CURVES ARE SUBJECT TO CHANGE WITHOUT NOTICE. EFFICIENCIES SHOWN ARE NOMINAL BOWL. GUARANTEED MINIMUM EFFICIENCIES PER H.I. LEVEL A.

