

PERFORMANCE CURVE

Models:
HE12W18
PE12W18
SE12W
V12W

Back-Pull-Out Casing
5-Blade Impeller
12" Discharge
18" Suction

CURVE	POWER (HP/KW)	SPEED (RPM)	IMPELLER DIAMETER
A	250/185	890	21.00" (533 mm)
B	200/150	860	21.00" (533 mm)
C	200/150	825	21.00" (533 mm)
D	150/110	775	21.00" (533 mm)
E	125 / 90	735	21.00" (533 mm)
F	100 / 75	675	21.00" (533 mm)
G	75 / 55	610	21.00" (533 mm)
H	60 / 45	575	21.00" (533 mm)
I	50 / 37	525	21.00" (533 mm)
J	40 / 30	490	21.00" (533 mm)
K	25 / 18.5	400	21.00" (533 mm)

DO NOT OPERATE PUMP IN DOTTED PORTION OF CURVES. PUMPS MAY EXCEED HP SHOWN IF OPERATED IN DOTTED PORTION OF CURVE. CURVES ARE SUBJECT TO CHANGE WITHOUT NOTICE. EFFICIENCIES SHOWN ARE NOMINAL BOWL. GUARANTEED MINIMUM EFFICIENCIES PER H.I. LEVEL A.

