

PERFORMANCE CURVE

**Models:
SE6W**

**Back-Pull-Out Casing
4-Blade Impeller
6" Discharge**

| CURVE | POWER (HP/KW) | SPEED (RPM) | IMPELLER DIAMETER |
|-------|---------------|-------------|-------------------|
| A | 25 / 18.5 | 1155 | 11.80" (300 mm) |
| B | 25 / 18.5 | 1155 | 11.50" (292 mm) |
| C | 20 / 15 | 1160 | 11.30" (287 mm) |
| D | 20 / 15 | 1160 | 10.90" (277 mm) |
| E | 15 / 11 | 1160 | 10.50" (267 mm) |
| F | 15 / 11 | 1160 | 10.00" (254 mm) |
| G | 10 / 7.5 | 1145 | 9.40" (239 mm) |
| H | 10 / 7.5 | 1145 | 9.20" (234 mm) |
| I | 7.5 / 5.5 | 1150 | 8.80" (224 mm) |

DO NOT OPERATE PUMP IN DOTTED PORTION OF CURVES. PUMPS MAY EXCEED HP SHOWN IF OPERATED IN DOTTED PORTION OF CURVE. CURVES ARE SUBJECT TO CHANGE WITHOUT NOTICE. EFFICIENCIES SHOWN ARE NOMINAL BOWL GUARANTEED MINIMUM EFFICIENCIES PER H.I. LEVEL A.

