Unmatched Reliability	Chopper Pumps Inquiry Form
Name:	Phone:
Application:	Pump Performance:
Type of Pump:    Vertical Wet Well: Length:Feet    Vertical Recirculator: Length:Feet    Horizontal  Vertical Pedestal    Submersible:  Explosion Proof	Capacity:GPM M³/Hr Head:feet meters psi
Guide Rail System	System Description
Hydraulic Submersible Cantilever: LengthFeet Self Primer	Pipe Diameter:inchmmDisch. Static:feetmetersDisch. Length:feetmeters
Property of Liquids:    Temperature:  °F    PH:  % SOLIDS:    Specific Gravity:	Inlet Static:feetmeters Inlet Length:feetmeters Header PSI:PSI Other:
Sump Dimensions:   ft deep xft wide xft long   M deep xM wide xM long   ft,meters diameter xdeep	Electric Motor Requirements: HP, RPM, Volts, Ph, Hz KW, RPM, Volts, Ph, Hz Enclosure Type:
Please tell us how you heard about Vaughan:	·
Fax, e-mail or mail form directly to: Vaughan Company, Inc. 364 Monte Elma Road Montesano, WA 98563 360-249-4042 Fax: 360-249-6155 e-mail: info@chopperpumps.com	



## TOTAL HEAD:

TDH = Pipeline Friction + Vertical Lift (H) + Velocity Head ( $V^2/2g$ )

- Pipeline Friction = [Pipe Length (ft) / 100] x friction factor (table on form V137)

Water friction tables are suitable for sewage & most water-borne slurries up to 5% solids. For high solids loadings & heavy organic sludge, use the biological friction table on form V137.

- Vertical Lift = feet up from supply tank low-water level to high level in discharge tank, or to the center of the open discharge pipe.
  - Note: Lift may be negative (-) if the pipeline is downhill.
    - Intermediate pipeline elevations (H2) higher than the final discharge can be ignored, except that the pump shutoff head must be higher than H2 in order to initiate flow.
- Velocity Head = Energy in the liquid being discharged due to its velocity.
  - Note: Usually ignored as insignificant in low head sump pump systems.
    - For high head systems, use nozzle manufacturer's printed data, or calculate using data as follows:
      - V = Velocity of the stream at the discharge diameter (ft/sec)
      - G = Acceleration due to gravity (32.2 ft/sec<sup>2</sup>)

## SPECIAL CASES:

Pipelines with valves & fitting, add appropriate equivalent pipe length. Pressurized supply or discharge tanks, add the discharge tank pressure, in feet, less any supply tank pressure, in feet, to the above Total Head calculation. Gauge pressure, in psi x 2.31 = head in feet. Very high solids content sludges & slurries, contact Vaughan on reliable test data for friction values.

Form V121 Rev 3 (05/2006)